

MCB

1. APPLICATION – WILL BE USED AT COMMERCIAL AND HOUSEHOLD LOCATIONS.
2. RANGE OF AVAILABILITY CURRENT (A) IS FROM 6 AMPS TO 63 AMPS.
3. NUMBER OF POLES AVAILABILITY 1, 2, 3 & 4
4. TYPES AVAILABILITY
 - TYPE B – SUITABLE FOR LIGHTING & SOCKETS OUTLETS
 - TYPE C – SUITABLE FOR MOTOR LOADS
 - TYPE D – SUITABLE FOR TRANSFORMER LOADS
5. TRIPPING CHARACTERISTICS
 - TYPE B – 3 – 5 TIMES TRIPPING CURRENT
 - TYPE C – 5 – 10 TIMES TRIPPING CURRENT
 - TYPE D – 10 – 20 TIMES TRIPPING CURRENT
6. MCB IS TRIPPING WITH OVERLOAD CURRENT OR SHORT CIRCUIT CURRENT
7. RATED BREAKING CAPACITY 6KA OR 10KA
RATED BREAKING CAPACITY ACCORDING TO IEC / EN 60898
8. SPECIAL FEATURES.
 - a. TOGGLE IS STANDARDIZED WITH COLOURS ACCORDING TO AMPS
 - b. AVAILABLE WITH TOGGLE ON / OFF INDICATOR (RED / GREEN)
 - c. TOGGLE CAN BE SEALED WITH “ON” OR “OFF” POSITION.